

Y76KPC

PHASE CONTROL THYRISTOR


Features:

- n Center amplifying gate
- n Metal case with ceramic insulator
- n Low on-state and switching losses

Typical Applications

- n AC controllers
- n DC and AC motor control
- n Controlled rectifiers

$I_{T(AV)}$ **4148 A**
 V_{DRM}/V_{RRM} **400-1000V**
 I_{TSM} **49.8 KA**
 I^2t **12400 10³A²S**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _f (°C)	VALUE			UNIT
				Min	Type	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Double side cooled, T _{hs} =55°C	125			4148	A
V_{DRM} V_{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	$V_{DRM} & V_{RRM}$ tp=10ms $V_{DSM} & V_{RSM} = V_{DRM} & V_{RRM} + 100V$	125	400		1000	V
I_{DRM} I_{RRM}	Repetitive peak current	$V_{DM} = V_{DRM}$ $V_{RM} = V_{RRM}$	125			200	mA
I_{TSM}	Surge on-state current	10ms half sine wave	125			49.8	KA
I^2t	I ² T for fusing coordination	$V_R = 0.6V_{RRM}$				12400	A ² s*10 ³
V_{TO}	Threshold voltage		125			0.82	V
r_T	On-state slop resistance					0.07	mW
V_{TM}	Peak on-state voltage	$I_{TM} = 5000A, F = 40KN$	125			1.17	V
dv/dt	Critical rate of rise of off-state voltage	$V_{DM} = 0.67V_{DRM}$	125			300	V/μs
di/dt	Critical rate of rise of on-state current	$V_{DM} = 67\%V_{DRM}$ to 4000A, Gate pulse $t_r \leq 0.5 \mu s$ $I_{GM} = 1.5A$ Repetitive	125			250	A/μs
I_{rm}	Reverse recovery current	$I_{TM} = 2000A, tp = 1000\mu s, di/dt = -20A/\mu s,$ $V_R = 50V$	125			220	A
t_{rr}	Reverse recovery time					22	μs
Q_{rr}	Recovery charge					2420	μC
I_{GT}	Gate trigger current	$V_A = 12V, I_A = 1A$	25	40		300	mA
V_{GT}	Gate trigger voltage			0.8		3.0	V
I_H	Holding current			20		300	mA
V_{GD}	Non-trigger gate voltage	$V_{DM} = 67\%V_{DRM}$	125	0.3			V
$R_{th(j-h)}$	Thermal resistance Junction to heat sink	At 180° sine double side cooled Clamping force 40.0KN				0.011	°C /W
F_m	Mounting force			35		47	KN
T_{stg}	Stored temperature			-40		140	°C
W_t	Weight					1100	g
Outline	KT73cT						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10

Outline:

